



# IN-TANK FUEL FILTER



### FEATURES:

- Positive dual filtration
- Non-woven fabric element, single or dual, for higher filtration capacity
- Stainless mesh secondary elements, 30 micron or 40 micron, single or double elements available
- Corrosion resistant to stale fuel, ethanol and water
- Excellent wicking ability to consume virtually all fuel from tank

## Walbro In-Tank Fuel Filters

Part #	Screens	Felt Filter	Fitting O.D.	Notes
125-527	1	1	5.5mm	
125-528	1	2	5.5mm	
125-529	1	1	5.5mm	
125-532	2	2	5.5mm	
125-535	1	1	5.5mm	
125-536	0	2	5.5mm	
125-540	2	2	5.5mm	
125-541	2	1	5.5mm	
125-552	0	1	5.5mm	
125-553	2	1	5.5mm	
125-555	2	2	5.5mm	
125-558	2	2	5.5mm	
125-567	2	2	5.5mm	
125-570	1	1	5.5mm	
125-577	1	1	5.5mm	Tail type filter
125-579	1	1	5.5mm	
125-580	1	1	5.5mm	125-579 w/rubber cap
125-582	1	2	5.5mm	Tail type filter
125-610	2	1	5.5mm	



**Walbro**  
**Worldwide Headquarters**  
 7400 N. Oracle Road, #310  
 Tucson, Arizona 85704-6342 USA  
 Telephone (520) 877-3000  
 Fax (520) 877-3006  
 Email: info@walbro.com

**Walbro North America**  
**North American Sales Office**  
 Email: sales@walbro.com

**Walbro Europe**  
**European Sales Office**  
 Email: europesales@walbro.com

**Walbro Japan**  
**Asian Sales Office**  
 Email: asiasales@walbro.com

**Walbro China**  
**China Sales Office**  
 Email: chinasales@walbro.com